



SOCIM
ANTINFORTUNISTICA

TECHNICAL DATA SHEET

NITRILE COATED GLOVE

COD. 3094T

Material: 100% polyester

Color: grey

Size: 6 - 7 - 8 - 9 - 10 – 11



Category fo belonging: II

Perfomances: EN 388/16 (mechanical risks)

CHECKS	LEVEL
ABRASION	4
CUT	1
RIP	3
DRILLING	1
EN ISO 13997 TDM	X



Maintenance instructions: The glove must be stored in a dry place away from heat sources. Avoid contact with solvent products which can cause alteration of the characteristics. In particularly severe conditions of use or in environments with special situations it is possible that the glove is subject to sudden and sudden degradation not foreseen by the manufacturer.










Cleaning: washing is not allowed.

Fields of use:

- ❖ **Automotive-mechanical industry**
- ✓ Intricate montages
- ✓ Sorting of small parts
- ✓ Installation of small screws and clips

- ❖ **Electronics**
 - ✓ Assembly of electronic componetns
 - ✓ Manipulation of microprocessors

- ❖ **Cosmetic and pharmaceutical idnustry**
 - ✓ Cosmetic preparations
 - ✓ Medical productions

Legenda		PROTEZIONE CHIMICA SPECIFICA			MICROORGANISM
<p>EN 388 RISCHI MECCANICI</p>  <p>LIVELLI DI PERFORMANCE 0-4 0-5 0-4 0-4 A-F (P)</p> <ul style="list-style-type: none"> Protezione contro gli urti Resistenza al taglio conforme alla norma ISO 13997 Resistenza alla perforazione Resistenza allo strappo Resistenza al taglio per tranciatura Resistenza all'abrasione 				<p>EN ISO 374-5</p>  <p>Protezione contro funghi e batteri</p>	
	<p>EN ISO 374-1 Type A</p>  <p>U V W X Y Z</p> <p>A Metanolo B Acetone C Acetonitrile D Diclorometano E Disolfuro di carbonio F Toluene G Dietilammina H Tetraidrofurano I Acetato di etile</p>	<p>EN ISO 374-1 Type B</p>  <p>X Y Z</p> <p>J n-Eptano K Idrossido di sodio 40% L Acido solforico 30% M Acido nitrico 65% N Acido acetico 99% O Ammoniaca 25% P Perossido di idrogeno 30% S Acido idrofluorico 40% T Formaldeide 37%</p>	<p>EN ISO 374-1 Type C</p> 	<p>EN ISO 374-5</p>  <p>Protezione contro funghi, batteri e virus</p>	
<p>EN 407 RISCHI TERMICI Calore e fuoco</p>  <p>LIVELLI DI PERFORMANCE 0-4 0-4 0-4 0-4 0-4 0-4</p> <ul style="list-style-type: none"> Resistenza ai grossi spruzzi di metallo fuso Resistenza ai piccoli spruzzi di metallo fuso Resistenza al calore radiante Resistenza al calore convettivo Resistenza al calore da contatto Comportamento al fuoco 	<p>EN 421 CONTAMINAZIONE RADIOATTIVA</p> 			<p>VIRUS</p>	
				<p>EN 511 RISCHI DOVUTI AL FREDDO</p>  <p>LIVELLI DI PERFORMANCE 0-4 0-4 0 o 1</p> <ul style="list-style-type: none"> Permeabilità all'acqua Resistenza al freddo da contatto Resistenza al freddo convettivo 	