



UNI EN ISO 9001:2015
Quality System Certified Company



TECHNICAL DATA SHEET PRODUCT

BASE COLORE

COLOURING PASTE FOR POLYESTER AND EPOXY ADHESIVES

BASE COLORE is a mixture of pigment in dispersion used for colouring the adhesives formulated by polyester resins and other thermosetting resins.

The pigments used for the formulation are selected through a continuous and thorough research to ensure good characteristics of "wetting".

Characteristic element in the selection of pigments is their non-toxicity.

FUNCTION

Colouring paste for adhesives/glues

LINE

ADHESIVES / GLUES

PROFESSIONAL

INDICATION

Colouring of adhesives based on Polyester or/and Epoxy resins

MATERIALS

Any kind of polyester and epoxy adhesive/glue

HOW TO USE

The paste-pigment must be mixed to the adhesive to be colored before applying the hardener/catalyst to the adhesive.

Add to the adhesive/resin the quantity of colour to obtain the requested shade.

Do not exceed 2-3% as a maximum dose of colour.

Mix carefully and slowly in order to obtain a texture of even colour and to avoid the inclusion of air bubbles into the texture.

COMPOSITION

Organic and inorganic pigments

TECHNICAL DATA

The percentage/ratio of use depends on the required final effect or the "correction" to be made to the basic colour of the adhesive.

The suggested maximum percentage/ratio is in the ratio of 3% to keep unchanged the adhesive capacity of the adhesive/glue.

STABILITY

Stored and kept into the original sealed container, at temperature between 15°C (59°F) and 25°C (77°F), sheltered from direct sunrays, far from heat sources and free flames, the product has no problems of stability.

COLOURS

Ivory, Blue, White, Yellow, Grey, Brown (light, chocolate, dark), Black, Red, Red-Beige, Green

Other eventual colours upon request and according to the quantity

PACKAGING

Plastic tube of 50 ml. (box of 16 tubes of the same colour)

LIMITED LIABILITY

The information provided derives from bibliography or from our laboratory experience and should be understood as broad indications and not as a formal guarantee. In particular, the liability for defective products, once the defect has been ascertained, is limited to the product purchase price only. We do not undertake any liability for implicit or explicit damage due to use of the product beyond our direct control.

A PRELIMINARY TEST IS ALWAYS RECOMMENDED BEFORE THE APPLICATION